


# SV-542F49



## Dimensions



## Product Summary

- 1/2.8" Sony IMX307 CMOS sensor
- Full HD resolution 1920 x 1080P
- Ultra low illumination 0.001Lux
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multiply WEB browser, PC Client, Mobile APP remote access
- Internal Microphone, reset button optional
- RJ45 100mbps network port, IEEE802.3af PoE.
- SD card slot optional
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 2 pcs Array IR Leds, IR distance 25-30 meters
- HD 3.6mm Fixed lens

## Major Specifications

\* Specifications are subject to change without prior notice.

Model Name		SV-542F49
Camera	Image Sensor	1/2.8" SONY IMX307 CMOS
	Effective Pixels	1920 (H) x 1080 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR/HDR(>120dB)
	White Balance	Auto/Indoor/Outdoor
	BLC	Support
	DNR	2D/3D DNR
	Other	Motion Detection, Privacy Mask, Mirror, flip
Encode	Embedded Solution	Mstar 335
	Video Standard	H.264/H.265
	Video Resolution	Main stream: 1080P@30fps , 720P@30fps Sub stream: D1/VGA/360P@30fps
	Video Bitrates	32Kbps - 5Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	OSD Overlay	Title and Time overlay
Leds	Leds	2PCS Array IR Led
	Light Distance	25-30 M
Lens	Focal length	HD 3.6mm Fix lens
Optional Function		Audio/SD card slot (support maximum 256GB SD card )
Network Services	Protocol	HTTP/RTSP/FTP/NFS/SMTTP/DHCP/NTP, etc.
	P2P	Yes
	Web	IE , Firefox, etc.
	Media	CMS, Android, IOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps,
	Power Supply	IEEE802.3af PoE, 12 VDC ± 10%
	Power Consumption	< 8 W
	Operating Temp.	-30℃-(+60)℃, 10%-90%RH