


# SV-695A63



## Dimensions



## Major Specifications

### Product Summary

- 1/2.8" Sony CMOS sensor
- 5MP realtime resolution 2560x1944P
- Low illumination 0.01Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR,Mirror, rotate, Defogging
- Multiply Style OSD Overlay,Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE,Firefox 32bit ESR, PC Client, Mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 10 pcs SMD Array IR Leds, IR distance 15 meters
- HD 3.6 mm fixed lens

\* Specifications are subject to change without prior notice.

Model Name		SV-695A63
Camera	Image Sensor	1/2.8" Sony CMOS
	Effective Pixels	5 megapixels
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto/Manual
	BLC /HLC	Support
	DNR	2D/3D DNR
Other	AGC,Motion Detection,Privacy Mask,Flip ,OSD overlay	
Encode	Video Standard	H.264/H.265
	Video Resolution	Main Stream:25fps@5MP(2592x1944)/4MP(2592x1520)/3MP, 30fps@1080P/720P Sub stream: 25fps@D1/VGA/360P/CIF, etc.
	Video Bitrates	512Kbps - 12Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	Built-in Mic	Optional
	OSD Overlay	Title and Time overlay
IR Led	IR Led	10 pcs SMD array IR Led
	IR Distance	15M
Lens	Focal length	3.6 mm fixed lens
Optional Function		POE, Audio
Network Services	Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
	P2P	Yes
	Web	IE , Firefox (32bit esr), etc.
	Media	CMS, Android, IOS
General	ONVIF	17.06 compatible
	Network Port	1-RJ45, 100Mbps, POE optional
	Power Supply	12 VDC ± 10%
	Power Consumption	< 8 W
Operating Temp.		-30 ℃-(+60) ℃, 10%-90%RH