

SVR-8008LF1



Product Summary

- 4K(8MP), 5MP, 4MP, 3MP, 2MP
- 1 HDMI, 1 VGA, 1 BNC
- UHD, QHD, FHD, SXGA, XGA
- H.265, H.264
- 4K(8MP), 5MP, 4MP, 3MP, 2MP, 960H
- 1 HDMI, 1 RCA
- 2 x USB 2.0
- 8fps (4K), 10fps (5MP), 30fps (2MP)

Major Specifications

Model Name		SVR-8008LF1
Video	Input	8 BNC ,IP
	Input Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP
	Output	1 HDMI, 1 VGA, 1 BNC
	Output Resolution	UHD, QHD, FHD, SXGA, XGA
Recording	Speed	2MP : 30fps/ch 3MP, 4MP : 15fps/ch 5MP : 10fps/ch 8MP : 8fps/ch
	Compression	H.265, H.264
	Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP, 960H
Playback	Speed	2MP : 208 fps 3MP : 146 fps 4MP : 117 fps 5MP : 86 fps 4K : 52 fps
	Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP, 960H
Audio	Input	8 RCA
	Output	1 HDMI, 1 RCA
Interface	Senser In / Out	8 / 1 - NC / NO
	USB	2 x USB 2.0
	PTZ / Keyboard	RS485 - Terminal Block
Network	Interface	Ethernet 10/100/1G
	Compression	H.265, H.264
	Speed	8fps (4K), 10fps (5MP), 30fps (2MP)
	Resolution	Normal 2MP, REC Video Bypass Max. 4K
System	OS	Embedded Linux (Built-in Flash Memory)
	Pre / Post-Alarm	5sec /5sec~5min
	Recording Mode	Continuous, Event, Schedule
	Data Search	Calendar, Multi Day / Time, Event, Go to Time
	Backup Interface	USB, Network
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
	Alarm Action	Buzzer, PTZ Preset, E-mail , SPOT, Relay, Event Popup, Push
	User	15 Users (Admin, User1 ~User14)
Network Viewer	NETUS-Pro(CMS), Web Viewer, Mac Viewer, NETUS-Eyes(iOS, Android)	
Storage	Primary	1 HDD
General	Size (W x H x D)	300 x 53 x 208 mm
	Weight(w/o HDD)	2 kg
	Temp / Humidity	5 ~ 40℃ /10% ~80%
	Power Supply	12V / 2A
	Power Consumption	24 Watts