Analogue, IP Hybrid DVR

SVR-8104FL

SECU-VISION



Product Summary

- Video Codec : H.264/H.265 / Audio Codec : G.711a
- Playback function : Fast forward / backward (2x, 4x, 8x,16x)
- Slow forward : (1/2x, 1/4x, 1/8x,1/16x)
- Display resolutionAnalog:5MP-Lite:20fps 4MP-Lite:30 fps 1080P/720P/960H:30fps
- IP:5MP/4MP/1080P/720P Single IP channel preview up to 2MP 30 fps
- HDMI 1（1024*768,1280*720,1280*1024,1440*900, 1920*1080,2560*1440(2K),3840*2160(4K)
- USB2.0*1(front) USB3.0*1+(rear)
- Audio 4 in /1 out
- HDD 1 SATA HDD, up to 8TB default (Design reserved 2HDD or 1HDD+1ESATA)
- Alarm 4 CH inputs /1CH output

Major Specifications

Model Name		SVR-8104FL
Recording Bandwidth	Inputs	4Mbps ~24Mbps (default is 4Mbps, decrease one Analog channel can increase 4Mbps) Total decoding performance 1080P 60fps
	out	48Mbps
	Analog video-input	4CH inputs
Live	IP Video Input	2ch,(only IP up to 6ch)
	Composite Video Input	up to 6 ch (Analog video + IP video)
Performance		
Installation wizard		Yes
Recording and Playback	Compression	Audio: G.711a Video : H.264/H.265
	Display resolution	Analog : 5MP-Lite:20fps 4MP-Lite:30 fps 1080P/720P/960H:30fps IP:5MP/4MP/1080P/720P Single IP channel preview up to 2MP 30 fps multi-channel preview only substream
	Speed	Analog : 5MP-Lite:12fps (each ch) 4MP-Lite:16fps(each ch) 1080P:15fps(each ch) 720P:PAL:25fps(each ch)/NTSC:30fps(each ch) IP:PAL:25fps(each ch)/NTSC: 30fps(each ch) Sub-stream Max ●PAL : 704*576:10fps(each ch)/NTSC : 704*480:10fps(each ch)
	Event	MD(Sensitivity Level 1~8)
		Videlo loss
		Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x)
		Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	5MPlite:48fps 4MPlite: 64fps 1080P: 60fps（Max 4CH playback） 720P:120fps（Max 4CH playback）
UI/Monitoring	Local	UI5.0
	WEB	IE10/11
	Mobile viewer	Rxcamview
	Push N/Atification	TUTK/RS
P/W Reset		Password Reset : Press 3 seconds Factory Reset : Press 10 seconds
Monitors	BNC	1 (704*576)
	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
	HDMI	1（1024*768,1280*720,1280*1024,1440*900,1920*1080,2560*1440(2K),3840*2160(4K)）
	Ethernet	1 RJ45 10/100 Base-T
	USB	USB2.0*1(front) USB3.0*1+(rear)
	Audio	4 in / 1 out
	E-sata	1 optional, not supported by default
	HDD	1 SATA HDD, up to 8TB default (Design reserved 2HDD or 1HDD+1ESATA)
	RS485	1
	Alarm Input/out	4 in /1 out
General		
OSD Language		More
Mechanical design	Dimension (WxDxH)	300X227X53mm
Electrical	Input Voltage/Current	1HDD:DC12V/2A
	Power consumption (excluding hard disk)	
Environmental	Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F) Humidity : Less than 90%RH