



Product Summary

- Video Codec : H.264/H.265 / Audio Codec : G.711a
- Playback function : Fast forward / backward (2x, 4x, 8x,16x)
- Slow forward : (1/2x, 1/4x, 1/8x,1/16x)
- Display resolution Analog : 8MP(15fps) 5MP(20fps) 4MP/1080P/720P/960H(30fps)
- IP resolution : 4K/4MP/1080P/720P, Single IP channel preview up to 4K 30 fps
- HDMI 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
- USB2.0*1(front) USB2.0*1+(rear)
- Audio 4 in / 1 out
- HDD 1 SATA HDD, up to 8TB default (Design reserved 2HDD)
- Alarm 4 CH inputs /1CH output

Major Specifications

Model Name		SVR-8104FL4K
Recording Bandwidth	Inputs	8Mbps ~36Mbps default is 16Mbps, decrease one Analog channel can increase 6Mbps Total decoding performance 4K 30fps
	out	48Mbps
	Analog video-input	4CH inputs
Live	IP Video Input	2ch,(only IP up to 6ch)
	Composite Video Input	up to 6ch (Analog video + IP video)
Performance		
Installation wizard		Yes
Recording and Playback	Compression	Audio : G.711a Video : H.264/H.265
	Display resolution	Analog : 8MP (15fps) 5MP (20fps) 4MP/1080P/720P/960H (30fps) IP : 4K/4MP/1080P/720P , Single IP channel preview up to 4K 30 fps Multi-channel preview only substream
	Speed	TBD Analog :8MP:7fps(each ch) 5MP:12fps(each ch) 4MP:15fps(each ch) 1080P:PAL:25fps(each ch)/NTSC:30fps(each ch) IP : PAL:25fps(each ch)/NTSC: 30fps(each ch) Sub-stream Max ●PAL : 704*576:10fps(each ch)/NTSC : 704*480:10fps(each ch)
	Event	MD(Sensitivity Level 1~8)
	Playback function	Videlo loss Beep, Email,Push notification to Mobile APP
	Playback	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
UI/Monitoring	Local	UI5.0
	WEB	IE10/11
	Mobile viewer	Rxcamview
	Push N/Atification	TUTK/RS
P/W Reset		Password Reset : Press 3 seconds Factory Reset : Press 10 seconds
Monitors	BNC	1 (704*576)
	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
	HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
	Ethernet	1 RJ45 10/100 Base-T
	USB	USB2.0*1(front) USB2.0*1+(rear)
	Audio	4 in / 1 out
	E-sata	1 optional, not supported by default
	HDD	1 SATA HDD, up to 8TB default (Design reserved 2HDD)
	RS485	1
Alarm Input/out		4 CH inputs /1CH output
General		
OSD Language		More
Mechanical design	Dimension (WxDxH)	300X227X53mm
Electrical	Input Voltage/Current	1HDD:DC12V/2A
	Power consumption (excluding hard disk)	
Environmental	Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F) Humidity : Less than 90%RH