

SVR4K-7616S



Product Summary

- Video Codec : H.264/H.265 / Audio Codec : G.711a
- Playback function : Fast forward / backward (2x, 4x, 8x,16x)
Slow forward : (1/2x, 1/4x, 1/8x,1/16x)
- Frame rate 4K:45fps 4MP:90fps 2MP:180fps
- HDMI 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
- USB2.0*1(front) USB2.0*1+(rear)
- Audio 1 out
- HDD 1 SATA HDD, up to 10TB (Design reserved 2HDD or 1HDD+1ESATA)
- Alarm 8 in /1 out optional, not supported by default

Major Specifications

Model Name		SVR4K-7616S
Video Recording Bandwidth	Resolution	8MP,5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P)
	Inputs	112M
	out	96M
Performance		
Installation wizard		Yes
Live/Playback	Compression	Audio: G.711a Video : H.264/H.265
	Frame rate	4K:45fps 4MP:90fps 2MP:180fps
	AI	yes
	Event	MD(Sensitivity Level 1~8) Videlo loss, Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward/backward(2x, 4x, 8x,16x) Slow forward(1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 16CH playback
UI/Monitoring	Local	UI5.0
	WEB	IE10/11
	Mobile viewer	Rxcamview
	Push N/Atification	TUTK/RS
Interface		
P/W Reset		Password Reset : Press 3 seconds Factory Reset : Press 10 seconds
Monitors	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
	HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
Connections	POE	16POE
	Ethernet	1 RJ45 100/1000 Base-T
	USB	USB2.0*1(front) USB2.0*1+(rear)
	Audio out	1
	E-sata	1 optional, not supported by default
	HDD	1 SATA HDD, up to 10TB (Design reserved 2HDD or 1HDD+1ESATA)
	Line in	1
	RS485	1 optional, not supported by default
	Alarm Input/out	8 in /1 out optional, not supported by default
General		
OSD Language		More
Mechanical design	Dimension (WxDxH)	300X302X54mm
	Input Voltage/Current	DC48V/3.75A
Electrical	Power consumption (excluding hard disk)	
	Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F) Humidity : Less than 90%RH